

www.bixolon.com



Retail



Hospitality



Ticketing



Kiosk

a Better Solution
for your Business™

Thermal Receipt Printer **SRP-350**

SRP-350 Highlights

- **Fast printing speed (up to 150mm per second)**
- **Easy drop in paper loading**
 - Simple paper jam removal
- **Various interface cards**
(Serial / Parallel / USB, USB+Serial / Ethernet, Powered USB)
- **User-friendly software tools**
 - Virtual Memory Switch Manager (VMSM)
 - NV image download
 - Full version of drivers supported
Windows Driver, OPOS Driver, JPOS Driver, Linux Cups Driver
- **2D barcode printing**
 - PDF417
 - QR Code

BIXOLON®

SRP-350

The SRP-350 is an ideal single station thermal receipt printer for Retail, Kitchen and Hospitality environments and also offers the same ultra-reliable quality that you have come to expect from BIXOLON.



MAIN FEATURES WITH SPECIFICATIONS

Fast printing speed

A printing speed of 150mm per second produces the receipts in shortest time without delaying customers or guests and receipts are cut automatically off the roll, making the job for case desk personnel easier and more efficient.

Easy paper loading



Roll changes at the SRP-350 is easy even for untrained personnel who master the process in a matter of moments. Paper threading is not necessary with this mode. Consequently, paper rolls of up to 80mm width are inserted in no time at all.

World-proven reliability

With an average performance of 37 million lines without failure, this printer gives you all reliability you need for long-term use and the auto-cutter for the SRP-350 is also guaranteed up to 1.5 million cuts with easy paper-jam removal.

Various Options


• WALL-MOUNT BRACKET



RWM-350

• SPLASH PROOF COVER

RSC-350




• MELODY BOX



RMB-100

• POWER SUPPLY COVER CASE

RSB-350



PRINT

- PRINTING METHOD : Direct thermal
- PRINTING SPEED : 150mm/sec
- RESOLUTION : 180 dpi (7 dot/mm)
- CHARACTER SIZE : Font A: 12 X 24 / Font B: 9 X 17
Korean: 24 X 24 / Chinese: 24 X 24
- CHARACTERS PER LINE : Font A: 42 / Font B: 56, Korean: 21 / Chinese: 21
- CHARACTER SET : Alphanumeric Character: 95
Extended Character: 128 X 34 pages
International Character: 32
- BARCODES
1D : EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Coda Bar, UPC-A, UPC-E / 2D: PDF417, QR Code

PAPER

- WIDTH : 80mm
- PAPER ROLL DIAMETER : Max Ø 83mm
- PAPER LOADING : Drop in paper loading

RELIABILITY

- PRINTER UNIT : 37,000,000 Lines
- TPH : 150 Km
- AUTO CUTTER : 1,500,000 cuts

INTERFACE : Serial(RS-232C, RS-485) / Parallel(IEEE 1284) / USB / USB+Serial / Ethernet / Powered USB

RECEIVE BUFFER : 4 Kbytes

NV IMAGE MEMORY : 256 Kbytes (Mono / Color)

USER DEFINE BUFFER : 12 Kbytes

DRIVER : Windows Driver, OPOS Driver, JPOS Driver, Linux Cups Driver

SENSOR : Paper Near End Sensor, Paper End Sensor, Cover Open Sensor

DRAWER PORT : 2 Drivers

POWER SUPPLY (SMPS) : AC 100~240V / DC 24V, 2.5A

DIMENSIONS : 145 X 195 X 146 (W X L X H mm)

OPERATING TEMPERATURE : 0 ~ 45°C

OPTIONS : Wall-mount bracket (RWM-350), Splash proof cover (RSC-350), Receipt melody box (RMB-100), SMPS built-in cover (RSB-350)

BIXOLON® www.bixolon.com

This publication carries product description without obligation and is not to be seen as a firm offer. All specifications and design are subject to change without notice. February 2009

BIXOLON Headquarters

Address #A-5F, Digital Empire Building, 980-3, Yeongtong-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-702, Korea
Tel +82 (0) 31 218 5500 Fax +82 (0) 31 218 5589
E-mail sales@bixolon.com

BIXOLON America Inc.

Address 1210 E. 223rd street Suite #330 Carson, CA 90745
Tel +1 858 764 4580 Fax +1 310 522 9319
E-mail sales@bixolonusa.com

BIXOLON Germany GmbH

Address Tiefenbroicher Weg 35, 40472 Düsseldorf
Tel +49 (0) 211 68 78 54 0 Fax +49 (0) 211 68 78 54 20
E-mail sales@bixolon.de